



**PT100 G1 MiniSeries ( 220-240V Single-phase Input )**

Model	Volt (V)	Power (KW)	Current (A)	Keyboard Model	N.W (kg)	G.W (kg)	Dimension L/W/H(mm)	InstallationSize a/b/d(mm)	CaseModel andSize	Picture
PT100-0R7G-1B	220	0.75	4.5	JP6E100						
PT100-1R5G-1B	220	1.50	7	JP6E100	1.26	1.3	151.6/100.6/123.5	145.7/94.6/Ø5.3	1S2 : 182/130/156	

**PT200 G1 GeneralSeries ( 220-240V Single-Phase Input )**

Model	Volt (V)	Power (KW)	Current (A)	Keyboard Model	N.W (kg)	G.W (kg)	Dimension H/D/W(mm)	InstallationSize a/b/d(mm)	CaseModel andSize	Picture (mm)
PT200-0R4G-1B	220	0.40	2.3	JP6E200						
PT200-0R7G-1B	220	0.75	4.5	JP6E200						
PT200-1R5G-1B	220	1.50	7	JP6E200	2	2.4	189.5/167/120	108/174/Ø5.4	2S1 : 249/180/217.8	
PT200-2R2G-1B	220	2.20	10	JP6E200						
PT200-004G-1B	220	4.00	16	JP6E200	3	3.5	220/183.5/150	138/209/Ø5.4	2S2 : 284/210/234.5	
PT200-5R5G-1B	220	5.5/7.5	20	JP6E200						
PT200-7R5G-1B	220	7.5/11	30	JP6E200	5.2	11.0	430/255/263	170/407/Ø9	2N2 : 490/323/305	

PS:


1, Voltagerange is  $\pm 15\%$ , G-1B Series Single phase input, G-3 Series 3-Phase input

2, PT200xxxG-XB, "B" Means build-in brake unit inside.




3, All Series have RS485 Card build-in inside.

4, Option OLED display add \$20 extra.


### PT200 G3/P3 General/Flowing Series ( 380-415V 3-Phase Input )

Model	Volt	Power	Current	Keyboard Model	N.W	G.W	Dimension	InstallationSize	CaseModel andSize	Picture (mm)
	(V)	(KW)	(A)		(kg)	(kg)	H/D/W (mm)	a/b/d(mm)		
PT200-0R7G-3B	380	0.75	3	JP6E200	2	2.4	189.5/167/120	108/174/Ø5.4	2S1 : 249/180/217.8	
PT200-1R5G-3B	380	1.50	4	JP6E200						
PT200-2R2G-3B	380	2.20	5	JP6E200						
PT200-004G-3B	380	4/5.5	9/13	JP6E200	3	3.5	220/183.5/150	138/209/Ø5.4	2S2 : 284/210/234.5	
PT200-5R5G-3B	380	5.50	13	JP6E200						
PT200-7R5P-3B	380	7.50	17	JP6E200						
PT200-7R5G-3B	380	7.50	17	JP6E200	5.2	5.8	285/208.5/180	167/272/Ø5.4	2S3 : 349/240/259.5	
PT200-011P-3B	380	11.00	25	JP6E200	5.2	5.8				
PT200-011G/015P-3B	380	11/15	25/32	JP6E200	9	10	345/230/203	150/325/Ø9	2N1 : 405/263/280	
PT200-015G/018P-3B	380	15/18	32/37	JP6E200	10	11				
PT200-018G/022P-3B	380	18/22	37/45	JP6E200	16.6	18	430/255/263	170/407/Ø9	2N2 : 490/323/305	
PT200-022G/030P-3B	380	22/30	45/60	JP6E200	17	18.5				
PT200-030G/037P-3	380	30/37	60/75	JP6E200	22.8	29	490/274/310	190/468/Ø10	2N3 : 550/370/324	
PT200-037G/045P-3	380	37/45	75/90	JP6E200	23	30				
PT200-045G/055P-3	380	45/55	90/110	JP6E200	45	53	640/330/370	250/610/Ø12	2N4 : 678/470/425	
PT200-055G/075P-3	380	55/75	110/150	JP6E200	50	59				
PT200-075G/093P-3	380	75/93	150/176	JP6E200	56	66	686/341/400	250/655/Ø12	2N5 : 730/500/423	
PT200-093G/110P-3	380	93/110	176/210	JP6E200	68	78.0				
PT200-110G/132P-3	380	110/132	210/250	JP6E200	88	99	786/353/500	300/748/Ø14	2N6 : 860/620/450	
PT200-132G/160P-3	380	132/160	250/300	JP6E200	110	130				
PT200-160G/187P-3	380	160/187	300/340	JP6E200	160	187	1000/400/600(Hanging), 1300/400/600(Standing)	370/935/Ø14	2N7 : 1025/720/500(Hanging), 1390/720/500(Standing)	
PT200-185G/200P-3	380	187/200	340/380	JP6E200						
PT200-200G/220P-3	380	200/220	380/415	JP6E200						
PT200-220G/250P-3	380	220/250	415/470	JP6E200	187	208	1160/400/650(Hanging) 1460/400/650(Standing)	370/1100/Ø14	2N8	
PT200-250G/280P-3	380	250/280	470/520	JP6E200						
PT200-280G/315P-3	380	280/315	520/600	JP6E200						
PT200-315G/355P-3	380	315/355	600/640	JP6E200	450	500.0	1650/480/830		2N9	
PT200-355G/400P-3	380	355/400	640/690	JP6E200						
PT200-400G/450P-3	380	400/450	690/740	JP6E200						
PT200-450G/500P-3	380	450/500	740/860	JP6E200						
PT200-500G/560P-3	380	500/560	860/950	JP6E200			1800/560/1000		2N10	
PT200-560G/630P-3	380	560/630	950/1100	JP6E200						



### PT200H3HeavyLoading Series ( 380-415V 3-Phase Input )

Model	Volt	Power	Current	Keyboard Model	N.W	G.W	Dimension	InstallationSize	CaseModel andSize	Picture (mm)
	(V)	(KW)	(A)		(kg)	(kg)	H/D/W(mm)	a/b/d(mm)		
PT200-R75H-3B	380	0.75	4	JP6E200	2	2.4	189.5/167/120	108/174/Ø5.4	2S1 : 249/180/217.8	
PT200-1R5H-3B	380	1.50	3.7	JP6E200						
PT200-2R2H-3B	380	2.20	5	JP6E200	3	3.5	220/183.5/150	138/209/Ø5.4	2S2 : 284/210/234.5	
PT200-004H-3B	380	4.00	9	JP6E200						
PT200-5R5H-3B	380	5.50	13	JP6E200	5.2	5.8	285/208.5/180	167/272/Ø5.4	2S3 : 349/240/259.5	
PT200-7R5H-3B	380	7.50	17	JP6E200	9	10.0	345/230/203	150/325/Ø9	2N1 : 405/263/280	
PT200-011H-3B	380	11.00	25	JP6E200	10	11.0				
PT200-015H-3B	380	15.00	32	JP6E200	16.6	18.0	430/255/263	170/407/Ø9	2N2 : 490/323/305	
PT200-018H-3B	380	18.00	37	JP6E200	17	18.5				
PT200-022H-3B	380	22.00	45	JP6E200	22.8	29.0	490/274/300	190/468/Ø10	2N3 : 550/370/324	
PT200-030H-3	380	30.00	60	JP6E200	23	30.0				
PT200-037H-3	380	37.00	75	JP6E200	45	54.0	600/300/360	200/580/Ø10	2N4 : 678/470/425	
PT200-045H-3	380	45.00	90	JP6E200	48	59.0				
PT200-055H-3	380	55.00	110	JP6E200	59	66.0	686/330/400	250/655/Ø12	2N5 : 730/500/423	
PT200-075H-3	380	75.00	150	JP6E200	67	75.0				
PT200-093H-3	380	93.00	176	JP6E200	89	99.0	786/353/500	300/748/Ø14	2N6 : 860/620/450	
PT200-110H-3	380	110.00	210	JP6E200	116	130.0				
PT200-132H-3	380	132.00	250	JP6E200	150	187.0	1000/400/600 (Hanging), 1300/400/600 (Standing)	370/935/Ø14	2N7 : 1025/720/500(Hangi ng),1390/720/500(St anding)	
PT200-160H-3	380	160.00	300	JP6E200	190	208.0				
PT200-185H-3	380	187.00	340	JP6E200						
PT200-200H-3	380	200.00	380	JP6E200						
PT200-220H-3	380	220.00	415	JP6E200	250	280.0	1160/400/650 (Hanging), 1460/400/650 (Standing)	370/1100/Ø14	2N8	
PT200-250H-3	380	250.00	470	JP6E200						
PT200-280H-3	380	280.00	520	JP6E200	350	400.0	1650/480/830		2N9	
PT200-315H-3	380	315.00	600	JP6E200						
PT200-355H-3	380	355.00	640	JP6E200						

**PT200 G2 GeneralSeries ( 220V 3-Phase Input )**

Model	Volt	Power	Current	Keyboard Model	N.W	G.W	Dimension	InstallationSize	CaseModel	Picture
	(V)	(KW)	(A)		(kg)	(kg)	H/D/W(mm)	a/b/d(mm)		
PI200-R7G-2B	220	0.75	5	JP6E200	2	2.4	189.5/167/120	108/174/Ø5.4	2S1 : 249/180/217.8	
PI200-1R5G-2B	220	1.50	7	JP6E200						
PI200-2R2G-2B	220	2.20	10	JP6E200						
PI200-004G-2B	220	4.00	16	JP6E200	3	3.5	220/183.5/150	138/209/Ø5.4		
PI200-5R5G-2B	220	5.50	20	JP6E200						
PI200-7R5G-2B	220	7.50	30	JP6E200	10	11.0	600/300/360	200/580/Ø10	2N4 : 678/470/425	
PI200-011G-2B	220	11.00	42	JP6E200						
PI200-015G-2B	220	15.00	55	JP6E200						
PI200-018G-2B	220	18.00	70	JP6E200	22	30.0	600/300/360	200/580/Ø10	2N4 : 678/470/425	
PI200-022G-2	220	22.00	80	JP6E200						
PI200-030G-2	220	30.00	110	JP6E200	50	70.0	600/300/360	200/580/Ø10	2N4 : 678/470/425	
PI200-037G-2	220	37.00	130	JP6E200						
PI200-045G-2	220	45.00	160	JP6E200						
PI200-055G-2	220	55.00	200	JP6E200	90	110.0	1000/400/600	370/935/Ø14	2N7 : 1025/720/500	
PT200-075G-2	220	75.00	260	JP6E200						
PT200-093G-2	220	93.00	320	JP6E200						
PT200-110G-2	220	110.00	380	JP6E200	110	150.0	1000/400/600	370/935/Ø14	2N7 : 1025/720/500	
PT200-132G-2	220	132.00	420	JP6E200						
PT200-160G-2	220	160.00	550	JP6E200						
PT200-185G-2	220	187.00	600	JP6E200	150	200.0	1000/400/600	370/935/Ø14	2N7 : 1025/720/500	
PT200-200G-2	220	200.00	660	JP6E200						
PT200-220G-2	220	220.00	720	JP6E200						

### PT200 G6/P6 General/Flowing Series ( 660V 3-Phase Input )

Model	Volt	Power	Current	Keyboard	N.W	G.W	Dimension	InstallationSize	CaseModel	Picture (mm)
	(V)	(KW)	(A)	Model	( kg)	(kg)	H/D/W (mm)	a/b/d(mm)		
PT200-030G/037P-6	660	30/37	35/45	JP6E200	45	54.0	600/300/360	200/580/Ø10	2N4 : 678/470/425	
PT200-037G/045P-6	660	37/45	45/52	JP6E200	50	58.0				
PT200-045G/055P-6	660	45/55	52/63	JP6E200	58	65.0				
PT200-055G/075P-6	660	55/75	63/86	JP6E200	66	78.0				
PT200-075G/093P-6	660	75/93	86/98	JP6E200	79	99	650/300/400	200/630/Ø10	2N5 : 730/500/423	
PT200-093G/110P-6	660	93/110	98/121	JP6E200	89	130	786/353/500	300/748/Ø14	2N6 : 860/620/450	
PT200-110G/132P-6	660	110/132	121/150	JP6E200	150	187				
PT200-132G/160P-6	660	132/160	150/175	JP6E200						
PT200-160G/187P-6	660	160/187	175/198	JP6E200						
PT200-185G/200P-6	660	187/200	198/218	JP6E200	187	208	1000/400/600(Hangi ng),1300/400/600(S tanding)	370/935/Ø14	2N7 : 1025/720/500(Hangi ng),1390/720/500(St anding)	
PT200-200G/220P-6	660	200/220	218/240	JP6E200						
PT200-220G/250P-6	660	220/250	240/270	JP6E200						
PT200-250G/280P-6	660	250/280	270/330	JP6E200	280	300.0	1160/400/650(Hangi ng),1460/400/650(S tanding)	370/1100/Ø14	2N8	
PT200-280G/315P-6	660	280/315	330/345	JP6E200						
PT200-315G/355P-6	660	315/355	345/370	JP6E200						
PT200-355G/400P-6	660	355/400	370/430	JP6E200						
PT200-400G/450P-6	660	400/450	430/490	JP6E200						
PT200-450G/500P-6	660	450/500	490/540	JP6E200						
PT200-500G/560P-6	660	500/560	540/600	JP6E200						
PT200-560G/630P-6	660	560/630	600/670	JP6E200						
PT200-630G/720P-6	660	630/720	670/760	JP6E200			1650/480/830		2N9	